Technical data

23226.EMKW33C3


Double row spherical roller bearings



Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring, tapered bore 1:12

ULTAGE

Visual(s)



Product definition

d	130 mm
D	230 mm
B	80 mm
d2	150.7 mm
D1	202.7 mm
rs min	3 mm
Number of lubrication holes	3
b	11.6 mm
k	5 mm
Associated sleeve reference	H2326
e	0.32
Y1	2.12
Y2	3.15
Y0	2.07
Radial clearance class	C3
Mass	13.38 kg
Brand	SNR

Product performance

Dynamic load, C	958 kN
Static load, C0	1,130 kN
Fatigue limit load, Cu	80.2 kN
Nref	1,900 Tr/min
Nlim	2,600 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.33 Hz
Characteristic outer ring frequency, BPF0	7.64 Hz
Characteristic inner ring frequency, BPFI	10.36 Hz

Abutment dimensions

da min	144 mm
da max	2.5 mm
db min	142 mm
Ce min	21 mm
Da max	216 mm
ra max	2.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .