Technical data

24034EAW33C5


Double row spherical roller bearings



Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring

ULTAGE

Visual(s)



Product definition

d	170 mm
D	260 mm
B	90 mm
d2	188 mm
D1	232.3 mm
rs min	2.1 mm
Number of lubrication holes	3
b	10.67 mm
k	5 mm
Associated sleeve reference	P0
e	0.31
Y1	2.21
Y2	3.29
Y0	2.16
Radial clearance class	C5
Mass	16.73 kg
Brand	SNR

Product performance

Dynamic load, C	1,120 kN
Static load, C0	1,580 kN
Fatigue limit load, Cu	97.4 kN
Nref	1,600 Tr/min
Nlim	2,400 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.6 Hz
Characteristic outer ring frequency, BPF0	10.65 Hz
Characteristic inner ring frequency, BPFI	13.35 Hz

Abutment dimensions

da min	180.2 mm
da max	2 mm
Da max	249.8 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .