Technical data

24044.EMW33C3


Double row spherical roller bearings



Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring

ULTAGE

Visual(s)



Product definition

d	220 mm
D	340 mm
B	118 mm
D1	303.4 mm
rs min	3 mm
Number of lubrication holes	3
b	14.1 mm
k	6 mm
Associated sleeve reference	P0
e	0.31
Y1	2.18
Y2	3.25
Y0	2.13
Radial clearance class	C3
Mass	38.4 kg
Brand	SNR

Product performance

Dynamic load, C	1,930 kN
Static load, C0	2,750 kN
Fatigue limit load, Cu	161 kN
Nref	1,200 Tr/min
Nlim	1,800 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.94 Hz
Characteristic outer ring frequency, BPF0	10.1 Hz
Characteristic inner ring frequency, BPFI	12.9 Hz

Abutment dimensions

da min	232.4 mm
da max	2.5 mm
Da max	327.6 mm
ra max	2.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .