Technical data

24128.EAW33


Double row spherical roller bearings



Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring

ULTAGE

Visual(s)



Product definition

d	140 mm
D	225 mm
B	85 mm
d2	156.2 mm
D1	197.6 mm
rs min	2.1 mm
Number of lubrication holes	3
b	10.05 mm
k	4.5 mm
Associated sleeve reference	P0
e	0.34
Y1	1.98
Y2	2.94
Y0	1.93
Radial clearance class	CN
Mass	12.77 kg
Brand	SNR

Product performance

Dynamic load, C	951 kN
Static load, C0	1,280 kN
Fatigue limit load, Cu	76.1 kN
Nref	1,600 Tr/min
Nlim	2,300 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.74 Hz
Characteristic outer ring frequency, BPF0	9.64 Hz
Characteristic inner ring frequency, BPFI	12.36 Hz

Abutment dimensions

da min	152 mm
da max	2 mm
Da max	213 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .