Technical data


30309.A


Single row tapered roller bearings

Tapered roller bearing, pressed steel cage



Visual(s)





Product definition

d	45 mm
D	100 mm
B	25 mm
C	22 mm
T	27.25 mm
d1	70.8 mm
a	21.4 mm
rs min	2 mm
r1s min	1.5 mm
e	0.35
Y2	1.74
Y0	0.96
Mass	0.98 kg
ISO 355 reference	T2FB045
Brand	SNR

Product performance

Dynamic load, C	115 kN
Rating life coefficient, A2	1
Static load, C0	131 kN
Fatigue limit load, Cu	16 kN
Nref	5,100 Tr/min
Nlim	7,500 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.27 Hz
Characteristic outer ring frequency, BPF0	6.57 Hz
Characteristic inner ring frequency, BPFI	9.43 Hz

Abutment dimensions

da max	59 mm
db min	55 mm
Da min	86 mm
Da max	91.5 mm
Db min	93 mm
Ca min	3 mm
Cb min	5 mm
ra max	2 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table