Technical data

32015.A


Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

ULTAGE



Visual(s)



Product definition

d	75 mm
D	115 mm
B	25 mm
C	19 mm
T	25 mm
d1	95.7 mm
a	25.3 mm
rs min	1.5 mm
r1s min	1.5 mm
e	0.46
Y2	1.31
Y0	0.72
Mass	0.88 kg
ISO 355 reference	T4CC055
Brand	SNR

Product performance

Dynamic load, C	16.72 kN
Rating life coefficient, A2	1
Static load, C0	160 kN
Fatigue limit load, Cu	19.6 kN
Nref	3,700 Tr/min
Nlim	5,900 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	10.14 Hz
Characteristic outer ring frequency, BPF0	12.24 Hz
Characteristic inner ring frequency, BPFI	14.76 Hz

Abutment dimensions

da max	83 mm
db min	83.5 mm
Da min	103 mm
Da max	106.5 mm
Db min	110 mm
Ca min	5 mm
Cb min	6 mm
ra max	1.5 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table