Technical data


33213.A


Single row tapered roller bearings

Tapered roller bearing, pressed steel cage



Visual(s)





Product definition

d	65 mm
D	120 mm
B	41 mm
C	32 mm
T	41 mm
d1	95 mm
a	29.5 mm
rs min	2 mm
r1s min	1.5 mm
e	0.39
Y2	1.54
Y0	0.85
Mass	1.99 kg
ISO 355 reference	T3EE065
Brand	SNR

Product performance

Dynamic load, C	203 kN
Rating life coefficient, A2	1
Static load, C0	283 kN
Fatigue limit load, Cu	34.5 kN
Nref	3,700 Tr/min
Nlim	5,800 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.4 Hz
Characteristic outer ring frequency, BPF0	8.1 Hz
Characteristic inner ring frequency, BPFI	10.9 Hz

Abutment dimensions

da max	74 mm
db min	75 mm
Da min	102 mm
Da max	111.5 mm
Db min	115 mm
Ca min	7 mm
Cb min	9 mm
ra max	2 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table