Technical data


6213.F605

Single row deep groove ball bearings



TOPLINE deep groove ball bearing, radial contact, pressed steel cage, open, limestone applications up to 350°C.

Visual(s)



Product definition

d	65 mm
D	120 mm
B	23 mm
d1	77.5 mm
D1	107.8 mm
rs min	1.5 mm
Radial clearance class	> C5
Mass	0.99 kg
Brand	SNR

Product performance

Dynamic load, C	0.01 kN
Static load, C0	0.01 kN
Fatigue limit load, Cu	0 kN
f0	14.4
Nlim	50 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	350 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.37 Hz
Characteristic outer ring frequency, BPF0	4.1 Hz
Characteristic inner ring frequency, BPFI	5.9 Hz

Abutment dimensions

da min	73 mm
Ce min	0 mm
Da max	112 mm
ra max	1.5 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr