Technical datasheet


NJ212.EG15C4

Single row cylindrical roller bearings



Single row cylindrical roller bearing, single direction for axial loads, separable, polyamide cage.

Visual(s)



Product definition

d	60 mm
D	110 mm
B	22 mm
E	100 mm
F	72 mm
d1	77.5 mm
D1	96.1 mm
rs min	1.5 mm
r1s min	1.5 mm
Radial clearance class	C4
Mass (without HJ ring)	0.84 kg
Brand	SNR

Product performance

Dynamic load, C	94 kN
Static load, C0	102 kN
Fatigue limit load, Cu	12.4 kN
Nref	5,400 rpm
Nlim	7,500 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.98 Hz
Characteristic outer ring frequency, BPF0	6.7 Hz
Characteristic inner ring frequency, BPFI	9.3 Hz

Abutment dimensions

da min	68 mm
da max	71 mm
db min	75 mm
dc min	80 mm
Da max	102 mm
ra max	1.5 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = Fr$

Equivalent static radial load

$P_0 = Fr$