


# Technical data

## UCPAE.203.CC

Bearing units

grey cast housing, radial insert ball bearing with socket set screws,seal with slinger

## Visual(s)



## Product definition

| | |
|---|---|
| **A** | 32 mm |
| **A1** | 19 mm |
| **B** | 31 mm |
| **d** | 17 mm |
| **Dz** | 54 mm |
| **E** | 10 mm |
| **G** | R1/8" |
| **H** | 33.3 mm |
| **H1** | 9 mm |
| **H2** | 64 mm |
| **J** | 50.8 mm |
| **L** | 65 mm |
| **L1** | 18 mm |
| **N** | M8 |
| **s1** | 15.5 mm |
| **S** | 12.7 mm |
| **Z** | 44.5 mm |

## Product performance

| | |
|---|---|
| **C** | 12.8 kN |
| **C0** | 6.65 kN |
| **T min.** | -20 °C |
| **T max.** | 100 °C |

## Other features

| | |
|---|---|
| **Weight** | 0.54 kg |
| **Recommended tightening torque for set screw** | 5.5 Nm |
| **Designation of housing** | PAE204N- |
| **Designation of bearing** | UC203G2 |
| **Designation of closed end cover** | SCC204 |
| **Designation of open end cover** | SCO204-17 |