
# Technical data

## UCT205-14

Bearing units

grey cast housing, radial insert ball bearing with socket set screws,seal with slinger

## Visual(s)



## Product definition

| | |
|---|---|
| **A** | 32 mm |
| **A1** | 12 mm |
| **A2** | 24 mm |
| **B** | 34 mm |
| **A5** | 19.7 mm |
| **d** | 22.22 mm |
| **G** | M6x1 |
| **H** | 89 mm |
| **H1** | 76 mm |
| **H2** | 51 mm |
| **H** | 89 mm |
| **L** | 97 mm |
| **L1** | 62 mm |
| **L2** | 10 mm |
| **L3** | 51 mm |
| **N** | 19mm |
| **N1** | 16 mm |
| **N2** | 32 mm |
| **s1** | 17 mm |
| **S** | 14.3 mm |
| **SW** | 3.18 mm |

## Product performance

| | |
|---|---|
| **C** | 14 kN |
| **C0** | 7.88 kN |
| **T min.** | -20 °C |
| **T max.** | 100 °C |

## Other features

| | |
|---|---|
| **Weight** | 0.81 kg |
| **Recommended tightening torque for set screw** | 3.7 Nm |
| **Designation of housing** | T205- |
| **Designation of bearing** | UC205-14G2 |