
Datasheet

AXISCRAFT - Supported bearing for ballscrew, bore d = 20 mm - BF/FF

BF20-C5

BF20-C5 | Block-type supported-end unit



Component identification

No.	Component	Qty
1	Housing	1
2	Deep-groove ball bearing	1
3	Snap ring	1

Configuration

Support position	**Supported side**
Bearing bore d1	**20 mm**
Installed bearing	**6004ZZ**
Retaining ring	**S20**
Support unit accuracy class	**C5**
Bearing precision class	**Not specified**
Support assembly mass	**0.77 kg**



Load ratings

Basic dynamic radial C

9.4 kN

Basic static radial C0

5.0 kN


Ratings apply to the installed 6004ZZ bearing, not the support assembly.

Datasheet

AXISCRAFT - Supported bearing for ballscrew, bore d = 20 mm - BF/FF

BF20-C5

Dimensions and mounting details



Dimensional specification

Dimension	Value
d1 - bearing bore	**20 mm**
L - housing depth	**26 mm**
B - overall width	**88 mm**
H - overall height	**60 mm**
b	**44 mm**
h	**34 mm**
B1	**52 mm**

Dimension	Value
H1	**50 mm**
E	**22 mm**
P	**70 mm**
d2	**6.6 mm**
X - drill	**9 mm**
Y - counterbore	**14 mm**
Z - counterbore depth	**8.5 mm**

Component details

Retaining ring

Type	**S20**
Quantity in assembly	**1 pc**
Installed bearing	**6004ZZ**

Technical notes

All dimensions in millimetres. Drawings are not to scale.

Radial ratings refer to the installed 6004ZZ bearing, not the support assembly.

Selection guide: ballscrew diameter 25-28 mm; bearing bore d = 20 mm.