Technical data


32308.A


Single row tapered roller bearings

Tapered roller bearing, pressed steel cage



Visual(s)





Product definition

d	40 mm
D	90 mm
B	33 mm
C	27 mm
T	35.25 mm
d1	63.2 mm
a	23.4 mm
rs min	2 mm
r1s min	1.5 mm
e	0.35
Y2	1.74
Y0	0.96
Mass	1.04 kg
ISO 355 reference	T2FD040
Brand	SNR

Product performance

Dynamic load, C	121 kN
Rating life coefficient, A2	1
Static load, C0	148 kN
Fatigue limit load, Cu	18 kN
Nref	5,600 Tr/min
Nlim	8,300 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.26 Hz
Characteristic outer ring frequency, BPF0	6.57 Hz
Characteristic inner ring frequency, BPFI	9.43 Hz

Abutment dimensions

da max	50 mm
db min	50 mm
Da min	73 mm
Da max	81.5 mm
Db min	82 mm
Ca min	3 mm
Cb min	8 mm
ra max	2 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table